Sample tender text for panels of Metecno Bausysteme GmbH

Item	Amount (m²)	Product/service	Prize per unit (€)	Total (€)
		Sandwich roof panel Hipertec external and internal side galvanised and coated steel sheet with non-combustible insulation core made of mineral wool with sealing tapes in the longitudinal joint. Cover width 1000 mm Class of building material: A2-s1-d0 non-combustible according to EN 13501-1. <u>External sheet:</u> t=0,60 mm, trapeze-profile, distance between ribs: 333 mm, ☐ 25 µm polyester, standard colours corrosion protection class III ☐ 50 µm polyester, standard colours corrosion protection up to class 5 <u>Internal sheet:</u> t=0,45 mm, S-profiled with stucco embossing DU polyester, MC 9002 corrosion protection class II <u>Core-/Panel thickness (s/d):</u> — <u>Thermal conductivity (U):</u> ☐ 60/98 mm — 0,707 W/m²K ☐ 80/118 mm — 0,535 W/m²K ☐ 100/138 mm — 0,430 W/m²K ☐ 120/158 mm — 0,360 W/m²K ☐ 150/188 mm — 0,289 W/m²K ☐ 200/238 mm — 0,218 W/m²K *U values with joint coefficient (Ψ) according to DIN EN 14509* Delivery and installation on steel- or wooden support construction according to approval, the installation guidelines of Metecno Bausysteme GmbH and the technical regulations of IFBS. Use stainless steel screws with EPDM-washers only. Sealing tapes, saddle caps and any necessary cuttings are to be taken into account. Roof pitch: Eaves height: m Panel length: m		

as of February 2026